

BT-210

SAFETY DATA SHEET

Version 1.1 Effective Date: 06/01/15

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: BT-210

Description: Boiler Water Treatment
Suggested Use: Industrial Water Treatment

Restrictions on Use: Do not mix with other industrial chemicals.

Supplier: Advanced Chemical Technology, Inc.

8728 Utica Avenue

Rancho Cucamonga, CA 91730 1-909-980-4556 or 1-800-527-9607

Fax: 1-909-980-9366

Emergency Phone: 1-800-255-3924 (CHEMTEL)

2. HAZARDS IDENTIFICATION

Telephone:

Classification

GHS Classification: Skin Corrosion (Category 1A)

Serious Eye Damage (Category 1) Acute Toxicity, Oral (Category 4) Acute Aquatic Toxicity (Category 3)

GHS Label Elements

Pictogram:

Signal Word: Danger

Hazard Statements: H314: Causes severe skin burns and eye damage

H302: Harmful if swallowed H402: Harmful to aquatic life

Precautionary Statements: P280: Wear protective gloves/ protective clothing/ eye protection/ face

protection.

P303+P361+P353: IF ON SKIN OR HAIR: Remove all contaminated clothing.

Rinse skin with water/shower.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P301+P330+P331: IF SWALLOWED: Rinse mouth. Do not induce vomiting.

P313: Get medical attention.

HMIS Classification: Health Hazard: 2

Flammability: 0 Physical Hazards: 0

NFPA Rating: Health Hazard: 2

Fire: 0

Reactivity Hazard: 0

Potential Health Effects



BT-210

SAFETY DATA SHEET

Version 1.1 Effective Date: 06/01/15

Inhalation: Vapor is irritating to the nose, throat, and mucous membrane.

Skin: Causes skin irritation. A single prolonged exposure is not likely to result in

harmful quantities being absorbed.

Eyes: Vapor will irritate the eyes. Liquid and mist can severely irritate or damage the

eyes and cause corneal burns.

Ingestion: This material is corrosive to the mouth and throat

3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Component</u> <u>CAS Number</u> <u>Concentration</u>

Potassium Hydroxide 1310-58-3 <3% Sodium tripolyphosphate 7758-29-4 3% Sodium sulfite 7757-83-7 <10%

Synonyms:

4. FIRST AID MEASURES

If inhaled: If inhaled, move person into fresh air. If not breathing, give artificial respiration.

Consult a physician.

Skin Contact: Take off contaminated clothing and shoes immediately. Flush skin with plenty of

water for at least fifteen minutes. Consult a physician.

Eye Contact: Flush eyes with plenty of water for at least 15 minutes and consult a physician.

Remove contact lenses if able to do so. Continue rinsing eyes during transport

to hospital.

If Ingested: Do NOT induce vomiting unless instructed to do so by a physician. Never give

anything by mouth to an unconscious person. Rinse mouth with water. Consult

a physician.

5. FIREFIGHTING MEASURES

Flammability Overview: Dried residue can thermally decompose giving off irritating and potentially toxic

fumes.

Flash Point: Not Applicable

Extinguishing Media: Use water-spray, alcohol-resistant foam, dry chemical, or carbon dioxide. Tailor

extinguishing media to surrounding fire.

Special Protective Equipment

for Firefighters:

Wear a self-contained breathing apparatus (SCBA) for firefighting if necessary.

Hazardous Combustion

Products:

Carbon monoxide, carbon dioxide and oxides of sulfur.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: Use personal protective equipment. Avoid breathing vapors, mist, or gas.

Always ensure adequate ventilation. Evacuate personnel to safe areas.

Environmental Precautions: Prevent further leakage or spillage if safe to do so. Prevent from entering drains



BT-210

SAFETY DATA SHEET

Version 1.1 Effective Date: 06/01/15

Advanced Chemical Technology, Inc.

and waterways. Discharge into the environment must be avoided.

Containment and Clean Up: Soak up with inert absorbent material and dispose of as hazardous waste. Keep

in suitable, closed containers for disposal. If assistance is needed call

CHEMTEL or emergency services.

7. HANDLING AND STORAGE

Safe Handling: Use personal protective equipment. Avoid breathing vapors, mist, or gas. Always ensure

adequate ventilation.

Safe Storage: Keep containers tightly closed in a dry well-ventilated place. Containers which are

opened must be carefully resealed and kept upright to prevent leakage. Store away from

incompatible materials.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits

Component	CAS Number	Exposure Limit	Basis
Potassium Hydroxide	1310-58-3	2 mg/m ³	ACGIH Threshold Value (TLV)
		2 mg/m ³	OSHA Table Z-1: Limits for Air Contaminants
		2 mg/m ³	NIOSH Recommended Exposure Limits
Sodium tripolyphosphate	7758-29-4	2mg/M ³	ACGIH Threshold Value (TLV)
		15mg/m3 8hr TWA	OSHA Table Z-1: Limits for Air Contaminants
		Not Established	NIOSH Recommended Exposure Limits
Sodium sulfite	7757-83-7	2 mg/m ³	ACGIH Threshold Value (TLV)
		2mg/M ³	OSHA Table Z-1: Limits for Air Contaminants
		Not Established	NIOSH Recommended Exposure Limits

Personal Protective Equipment

Eye Protection: Wear tightly fitting safety goggles or safety glasses with a full-face shield. Use

equipment for eye protection tested and approved under appropriate government standards such as NIOSH. Have eye-wash stations available

where eye contact can occur.

Hand Protection: Handle with chemical-resistant gloves. Gloves must be inspected prior to use.

Dispose of contaminated gloves. Wash and dry hands after use.

Skin Protection: Protect skin by wearing pants, close toe shoes and long sleeves. The type of

protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. Safety showers

should be located in the work area where skin contact can occur.

Respiratory Protection: Where risk assessment shows air-purifying respirators are appropriate, use a

NIOSH-approved full-face respirator with appropriate cartridges. For oxygen deficient atmospheres, use a NIOSH approved air-supplied respirator.

Respiratory protection may be needed for non-routine or emergency situations. Respiratory protection must be provided in accordance with OSHA 29 CFR

1910.134.

General Controls: Always ensure adequate ventilation and that working areas contain safety

showers and eye wash stations. Handle material in accordance with good

industrial hygiene and safety practices.



BT-210

SAFETY DATA SHEET

Version 1.1 Effective Date: 06/01/15

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Liquid

Color: Light to Dark Amber liquid

Odor: Bland

Odor Threshold: Not Established

pH: 12.3

Melting/Freezing Point: Not Established

Boiling Point: 212°F

Flash Point: Not Established

Evaporation Rate: 1

Flammability (solid, gas):

Flammability/Explosion Limits:

Vapor Pressure @ 20°C:

Vapor Density:

Specific Gravity:

Not Established
23.75 mmHg
0.62 @ 68°F
1.1694

Density: Not Established

Solubility in Water: Soluble

Partition Coefficient:
Autoignition Temperature:
Decomposition Temperature:
Viscosity:

Not Established
Not Established
Not Established

10. STABILITY AND REACTIVITY

Chemical Stability: Stable under recommended storage conditions.

Conditions and Materials to

Avoid:

Compatible with most boiler water treatment compounds at use dosages.

Do not mix with other industrial chemicals.

Hazardous Decomposition

Products:

Carbon monoxide, carbon dioxide and oxides of sulfur.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Component	CAS Number	Test	Toxicity
Potassium Hydroxide	1310-58-3	Oral LD50 (Rat)	273 mg/kg
		Skin - Draize (Rabbit)	50 mg (24 hr) – Severe skin irritation
		Inhalation LC50	Not Established
Sodium tripolyphosphate	7758-29-4	Oral LD50 (Rat)	Not Established
		Skin - Draize (Rabbit)	Not Established
		Inhalation LC50	Not Established
Sodium sulfite	7757-83-7	Oral LD50 (Rat)	Not Established
		Skin - Draize (Rabbit)	Not Established
		Inhalation LC50	Not Established

Potential Health Effects

Inhalation: Vapor is irritating to the nose, throat, and mucous membrane.

Skin: Causes skin irritation. A single prolonged exposure is not likely to result in



BT-210

SAFETY DATA SHEET

Version 1.1 Effective Date: 06/01/15

harmful quantities being absorbed.

Eyes: Vapor will irritate the eyes. Liquid and mist can severely irritate or damage the

eyes and cause corneal burns.

Ingestion: This material is corrosive to the mouth and throat

Signs and Symptoms of

Exposure:

Burning sensation. Nausea. Cough. Wheezing. Laryngitis. Shortness of breath. Spasm, inflammation, and edema of the larynx. Spasm, inflammation, and edema of the bronchi. Pneumonitis. Pulmonary edema. Material is extremely destructive to the tissue of the mucous membrane, upper respiratory tract, eyes,

and skin. Headache.

Chronic Effects of Long-term

Exposure:

Not Established

Carcinogenicity: No component of this product at levels greater than 0.1% is identified as

carcinogenic by IARC, ACGIH, or OSHA.

12. ECOLOGICAL INFORMATION

Acute Ecotoxicity

Component	CAS Number	Organism	Ecotoxicity
Potassium Hydroxide	1310-58-3	Mosquito fish	24 hr LC50 = 80mg/L
Sodium tripolyphosphate	7758-29-4	Not Established	Not Established
Sodium sulfite	7757-83-7	Not Established	Not Established

Ecological Effects

Persistence and Degradability: Inorganic components will mineralize. Organic components will degrade with

exposure to sunlight and oxygen.

Bioaccumulation Potential: Not expected to bio-accumulate

Mobility in Soil: Not Established

Other Adverse Effects: Harmful to aquatic life. The damaging effects are mostly the consequence of the

increase in pH of the water.

13. DISPOSAL CONSIDERATIONS

Disposal: Surplus and non-recyclable material should be treated as hazardous waste and be

disposed of by a licensed disposal company. Material should be disposed in accordance with all local, state, and federal regulations. Regulations vary by region. Do not release

into sewers or waterways.

Contaminated Packaging: Dispose of as unused product.

14. TRANSPORT INFORMATION

DOT Information

Proper Shipping Name: Corrosive liquid, n.o.s. (potassium hydroxide)

UN Number: 1719



BT-210

SAFETY DATA SHEET

Version 1.1

Effective Date: 06/01/15

Hazard Class: 8 Packing Group: II

Reportable Quantity (RQ): Potassium Hydroxide: 1000lbs

Marine Pollutant: Not Established

Note: Regulated for both bulk and non-bulk.

15. REGULATORY INFORMATION

US Federal

SARA 302 Components: This product does not contain a Section 302 substance subject to Emergency

Planning Notification/Threshold Planning Quantities

SARA 311/312 Hazards: Immediate Health Hazard

SARA 313 Components: This product does not contain a Section 313 listed toxic chemical subject to

release reporting requirements.

TSCA Inventory: All chemical components are listed on TSCA Inventory.

European Union

EC Inventory: None Listed

State Regulations

CA Prop 65: This product does not contain chemicals currently on the California list of known

carcinogens and/or reproductive toxins.

16. OTHER INFORMATION

SDS Version: 1.1
Revision Date: 06/01/15

Disclaimer: The information contained in this document was carefully compiled and is

believed to be accurate. The information represents the present state of our knowledge and is applicable to the product with the regard to appropriate safety precautions. However, it does not represent any guarantee of the properties of the product. Advanced Chemical Technology, Inc. shall not be held liable for any damages resulting from handling or from contact with the above product. It is the responsibility of the purchaser to determine the suitability of the product for their particular purposes. Nothing contained herein shall be construed to be a recommendation to use, or as a license to operate under, or to infringe any existing patents. For product information call Advanced Chemical Technology,

Inc.,1-909-980-4556.